



GUANGDONG BOSHUN BELTING CO.,LTD.

博力顺  
BO LI SHUN

## Product Data Sheet

Type: 30P21-21N FDA

<b>Main industry segments</b>
Food

<b>Applications</b>
-

<b>Color code</b>
RAL 9003



<b>Product structure</b>	
<b>Top cover</b>	
-Thickness	0.7 mm
-Material	Polyvinyl chloride (N-PVC FDA)
-Features	Smooth, Oil and fat resistant, FDA
-Color	White
-Surface	Smooth
-Hardness	65° ShoreA
<b>Bottom cover</b>	
-Thickness	0.8 mm
-Material	Polyvinyl chloride (N-PVC FDA)
-Features	Non adhesive, Oil and fat resistant, FDA
-Color	White
-Surface	Diamond
-Hardness	75° ShoreA

<b>Technical data</b>	
Total thickness	3.0 mm
Number of plies	2
Weight	3.6 kg/m <sup>2</sup>
Maximum width	3500 mm
Effective pull at 1% elongation	10 N/mm
Breaking strength	180 N/mm
Twisting force	16 N/mm
Temperature range	-10 °C ~ +80 °C

<b>Minimum roll diameter</b>	
Normal flexion	50 mm
Counter flexion	80 mm

<b>Characteristic</b>			
Slide	Yes	Guides	Yes
Roller	Yes	Cleats	Yes
Trough	Yes	Sidewalls	Yes
Antistatic	No		
Oil and fat resistant	Yes		
FDA	Yes		

## Product photos



## Joining methods

Double Finger

## Disclaimer

All data are approximate values and defined under the following standard climatic conditions. 23 °C, 50 % relative humidity (ISO 554).

All informations are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. Due to the fact that Boshun Belting has no control of use, we will not assume any liability concerning the suitability and process ability of the products mentioned herein. This also applies to defects, damages, consequential damages, and other consequences

Issued: 2019.02.19

Last update: 2019.03.21

[www.boshunbelting.com](http://www.boshunbelting.com)

[info@boshunbelting.com](mailto:info@boshunbelting.com)